

# VCNM-H90 / VCNM-H92



## HDMI Extender Over LAN

### ► Specifications

	VCNM-H90	VCNM-H92
Signal Input	Ethernet + USB	
Signal Output	HDMI	
Max. Resolution	1920x1080 1600x1200	1920x1200 2048x1152
LED	Dual Color x 1+ Blue x 1	
Connector (In)	RJ-45 + USB-B	
Connector (Out)	HDMI	
Enclosure	Metal	
DDC2B Support	Yes	
Power Consumption (Max.)	DC 5V, 800mA	
Dimensions H x W x D (mm)	23 x 110 x 66	

### ► Features

- Extend HDMI signal transmission by using the existing LAN system without additional wiring
- Easily add extra display(s) via the Ethernet (or USB) port
- Small profile for convenient installation and save space
- Up to 4 Units can be daisy chained and connected to an Ethernet Hub at a time
- Perform the multiple windows on the multiple displays and increase the productivity like never before
- Demonstrate media files and DVDs in either extend or clone mode
- Support the high resolution up to UXGA(1600 x 1200)/ Full HD (1920 x 1080) and 2048 x 1152 for certain models
- Easy to get and install the standard cable at lower cost
- Fully support Windows 2000 SP4, Windows XP SP2 or SP3, Windows Vista SP1/SP2, Windows 7 32-bit and 64-bit editions
- Support Intel-based Mac OS 10.4/10.5 for the video+Audio extending via USB connection
- Ideal for applications on public broadcasting, exhibits, retail stores, courtrooms, classrooms, boardrooms, stock tickers, bus stations, etc.

### ► Connection Pattern

